



SOLIDSTART®
ENGINEERED WOOD LSL

IND 38

LP® SolidStart® LSL Customized To Your Needs

LP® SolidStart® Laminated Strand Lumber (LSL) IND 38 is intended for a wide variety of general applications. IND 38 is lighter than our structural grades of LSL while maintaining the same consistency of dimensions and remaining free of the defects of sawn lumber like knots, warp and wane. Trimming out defects and culling unusable pieces is not necessary with LP SolidStart LSL products. You get what you order — nothing less.

Available in thicknesses from $\frac{7}{8}$ " to $3\frac{1}{2}$ ", lengths up to 64', and widths from $3\frac{1}{8}$ " to 48", LP SolidStart LSL IND 38 is a great choice for:

- Shelving and retail displays
- Decorative panels for architectural highlights
- Upholstered furniture frame components
- Bed box spring components
- Domestic and export packaging, bracing, and blocking
- Substrate for counters, tables, pool tables, and bowling alleys
- Mats and pads to distribute loads
- Travel trailer and RV components
- Cabinet components and speaker boxes

LP SolidStart LSL & The Environment

- LP SolidStart LSL is made from wood—a renewable, natural resource
- Our wood procurement process targets small, fast growing trees that can be replenished more quickly than larger, older trees
- We use SFI® certified forest management and fiber sourcing systems to help ensure that our wood comes from well-managed forests; LP SolidStart LSL is certified to the SFI chain-of-custody standard
- The entire log is used in our manufacturing process; all wood waste is repurposed or used to help fuel our mills
- We only use low-emitting, safe resins in the manufacture of LP SolidStart LSL, and do not add urea-formaldehyde

- Wide variety of general applications
- Free of defects like knots, warp, and wane
- Available in custom thicknesses, lengths, and widths to minimize your waste
- Accurate, consistent sizes
- Available in unsanded, one-side sanded, or two-side sanded

Challenge us to find the right solution for you!



General

LP® SolidStart® Laminated Strand Lumber (LSL) IND 38 is intended for a variety of general applications that do not require specific structural properties. If specific structural properties are needed, consider one of our structural LSL products.

Density

The rolling average density target at time of manufacture is 38 pounds per cubic foot (pcf). The density for individual pieces can vary from the target average density. LP may, at its option, choose to provide LSL of higher average density.

Mechanical & Physical Properties

IND 38 will be free from delamination at the time of manufacture. **No other properties are represented and any properties evaluated from one sample or lot should not be assumed to be representative of those for any other sample or lot.** Properties not represented include but are not limited to bending, stiffness, tension, compression, shear, split resistance, dimensional stability, swell performance, moisture content, etc.

Dimensions for LSL

Unless mutually agreed to and specifically noted, dimension targets and tolerances will be as per *LP SolidStart Tech Note "Dimensional Tolerances of Engineered Wood Products."*

Texture, Voids and Color

Unless specifically noted, surfaces will be unsanded. Due to the size, thickness and orientation of the strands, voids will be present on both the face and edges of finished panels. Strand species and color may vary by production lot.



Markings

IND 38 will bear no grade marks or it may include marks indicating the product is not intended for structural use. Custom markings may be applied by mutual agreement in certain cases. Re-grading IND 38 for use in any structural application or re-marking IND 38 in any way that implies structural adequacy is prohibited.

Wrap

LP wrap or plain white wrap is available at the buyer's discretion.

Sealer

Unless mutually agreed to and specifically noted, no end, edge, or surface sealer will be applied.

Suitability

It is the sole responsibility of the buyer to determine if IND 38 is suited for the particular end-use prior to purchasing. IND 38 may not be used or resold for any structural applications.

Warranty

LP warrants that as of the date of their manufacture, these Products meet the specifications published in this document. **ALL OTHER WARRANTIES, EXPRESS AND IMPLIED, ARE HEREBY DISCLAIMED INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. ANY CLAIM FOR BREACH OF THIS WARRANTY MUST BE MADE TO LP WITHIN 120 DAYS OF SHIPMENT OF THE PRODUCTS FROM LP'S MILL. DAMAGES FOR BREACH OF WARRANTY SHALL IN NO EVENT EXCEED THE PURCHASE PRICE PAID TO LP FOR THE AFFECTED PRODUCTS.**

For more information on LP products, visit our website at LPCorp.com.

Phone: 1-888-820-0325

Fax: 1-877-523-7192

Email: Customer.Support@LPCorp.com

Web: LPCorp.com